

CERTIFIED PDF

DIECUT

- Line of 0.5 pt in Pantone 3405CV and on **overprint**.
- A **standard** bore (hole) is Ø 5 mm and 5 mm from the cutting edge.
If it's not standard ask for more specifications concerning the accessories related to the labels.

LAYOUT

- Text and/or images at least 2 mm from the cutting edge.
- Line thickness at least 0.2 pt.

BLEED/TRAP

- 2 mm for labels, stickers etc.
3 mm for brochures, flyers etc.
5 mm for banners, posters, packaging, potcovers etc.

COLOUR USE

- **CMYK**. When using PMS, clearly state the **PMS number** in the assignment.
Tip. For large black surfaces choose **black: C60% M30% Y20% K100%**.

PLEASE NOTE!

- No **extra** whitespace around the CPDF (Layout in clean format)
- In case of printing the backside 100% black. Please note **no** CMYK structure
- Always leave space for the product code. Font size of the product code must be **at least 9 points!**

OPEN FILE

PACKAGE

- Create a package in InDesign and Illustrator from the open file so that all links and fonts are delivered as well.

FONTS

- Please note: Fonts that are used in graphics must be delivered as well.
These fonts are not included when making a Package from InDesign.

IMAGES

- Always deliver images in 300 DPI and CMYK colour structure.

SUPPLY OPTIONS

WETRANSFER

- Direct via upload to the relevant contact person.

MAIL

- Please note that when delivering fonts, kindly send them as a zip file.

QUESTIONS

- We are happy to help! T **+31 (0)75 64 76 419**
E **dolores.camposkrook@floramedia.com**

In addition to the supplied files, please provide a list of your products in a Word and/or Excel-file.